

AD 633 630

USAARU REPORT NO. 66-7

EXPECTED INJURY RATES FOR  
EXPERIMENTAL AIRBORNE OPERATIONS

By

R. A. Avner, 1st Lt., MSC

JUNE 1966

U. S. ARMY AEROMEDICAL RESEARCH UNIT  
Fort Rucker, Alabama

U. S. Army Medical Research and Development Command

Distribution Statement. Distribution of this document is unlimited. Citation of names of commercial equipment or materials does not constitute an official endorsement or approval of the use of such items.

AD \_\_\_\_\_

USAARU REPORT NO. 66-7

EXPECTED INJURY RATES FOR  
EXPERIMENTAL AIRBORNE OPERATIONS

By

R. A. Avner, 1st Lt., MSC

JUNE 1966

U. S. ARMY AEROMEDICAL RESEARCH UNIT  
Fort Rucker, Alabama

U. S. Army Medical Research and Development Command

Distribution Statement. Distribution of this document is unlimited. Citation of names of commercial equipment or materials does not constitute an official endorsement or approval of the use of such items.

# ABSTRACT

Probability of injury for Army paratroopers under conditions of full combat load and unprepared drop zone was estimated to be .006 (standard error = .002,  $N = 5,253$ ). Tables were computed to allow tests of departure from this rate under experimental conditions involving up to 50 jumpers.

APPROVED:



WILLIAM P. SCHANE

Lt Colonel, MC

Acting Commander

## TABLE OF CONTENTS

Introduction and Purpose	1
Testing departures from standard injury rates	2
Use of table	2
Production of table	3
Table "Probability of "n" injuries among "N" jumpers ( $P = .006$ )"	4
References	6
Distribution List	
DD Form 1473	

## EXPECTED INJURY RATES FOR EXPERIMENTAL AIRBORNE OPERATIONS

### INTRODUCTION AND PURPOSE

Superior equipment and training have led to an extremely low injury rate for U. S. Army parachutists. Under general unit training conditions about 1.7 injuries would be expected for every 1,000 jumps ( $P = .0017$ , standard error = .0002,  $N = 137,966$ ). Under conditions of full combat load and unprepared drop zone this rate increases to about 6 injuries per 1,000 jumps ( $P = .006$ , standard error = .002,  $N = 5,253$ )\*. The latter rate is probably typical of what can be expected under these more severe conditions. Both British Army parachutists (Whittingham) and U. S. Forest Service "smokejumpers" (King) are also reported to have an injury rate of about .005 under similar severe conditions.

Base injury experience has several uses in development of new airborne equipment or techniques. In the case of innovations intended to increase safety, it serves as a basis for measurement of improvement. In the case of innovations intended to meet situations which are more hazardous than usual, it can serve as a basis for measure of the "loss" or "payment" exacted (i.e., increased injury rate) for the "gain" attained (the ability to meet the new situation).

In either case, it is usually not economically feasible to evaluate new developments by use of samples of the size upon which the base rate has been determined. Use of smaller samples (e.g., 50 or fewer jumps) leads however to a less precise estimate of the injury rate. With small samples the injury or non-injury of a single man can make relatively enormous changes in the observed injury rate. If one out of a group of ten men is injured the observed injury rate for this group is 10% (or 100 per 1,000). Yet, if this is the only injury in ten groups of ten men each the observed rate is only 1% for this larger group of 100 men. Thus, there is a possibility that even for low general injury rates some small samples will occasionally show much higher observed rates. It is the purpose of this report to show with exactly what probability relatively large observed rates of injuries might occur in small samples from a population in which the true injury rate is relatively small. The major use of such information is in evaluation of ongoing programs. It is undesirable to terminate an experiment because of an "excessive" injury rate when in fact the

\* Almost exactly half of these injuries were severe enough to require evacuation to permanent medical facilities and subsequent hospitalization. There were no fatalities.

injury rate is not significantly different from that expected by chance variation in the base rate. It is even more undesirable not to terminate an experiment simply because the actual number of injuries is small when this number indicates an injury rate significantly in excess of the acceptable rate.

## TESTING DEPARTURES FROM STANDARD INJURY RATES

If production of injuries is assumed to occur at random with a fixed probability in a given sample group, the number of injured in this sample group will follow the binomial distribution. Normal approximations to the binomial unfortunately have relatively large errors when  $P$  approaches zero or unity even for reasonably "large" samples of  $N = 100$ . It is therefore necessary to perform any tests by use of the appropriate exact binomial distribution.

The most efficient manner in which such tests could be run is probably some form of sequential analysis (Wald) in which small samples are observed in sequence until the hypothesis of "no departure from standard rates" is either accepted or rejected. Unfortunately one of the conditions of military parachuting is usually that jumping is performed in moderately sized groups (20 to 50 men). Jumps made by smaller groups could probably not be used for a valid estimate of the results of jumps made under more typical conditions. Thus decisions must usually be based on one or two independent jumps by groups totalling less than fifty men.

The inclosed binomial table gives the expected probability of varying numbers of injuries for groups of up to 50 jumpers when the true injury rate is 6 per 1,000.

## USE OF TABLE

The major use of the table is in determining if an observed injury rate is significantly higher than the expected combat-load injury rate. If it has been decided that the presence of a significantly higher rate is unacceptable, such a finding would support the termination of the test.

The procedure to be used consists of two steps. First a probability value is chosen which corresponds to how frequently the experimenter is willing to mistakenly halt the experiment when the injury rate is actually no more than normal. This is called the "alpha level" in statistical terminology. An alpha level of .01 would indicate that the experimenter is willing to have this error happen once in every 100 tests, a level of .001 indicates once in every 1000 tests, and so forth. Second, following a jump, the number of injuries is counted and the tabled probability for

this many or more injuries in a group of the size used is determined. If this probability is less than the alpha level the experiment is halted, if it is more, there is no significant difference (at the level tabled) between the observed and "standard" injury rate.

If more than one group jumps (up to 50 total) the total injuries and size of the groups may be combined for a more reliable test. This combination is valid only if each of the men jump only once (the same man must not be a member of more than one of the groups).

Choice of alpha level will depend on the objective of the tests. If safety is of first importance the alpha level will be high (e.g., .15 or even .20). If safety is of importance secondary to another objective, the alpha level will be low (e.g., .01, .001, or even .0001).

Examples: 1. (a) alpha level chosen to be .01

(b) Observation: 26 men jump, 2 are injured (probability of 2 or more injuries when the true injury rate is .006 is .010633, as given by the table).

(c) Conclusion: do not halt experiment - .010633 is greater than .01

2. (a) alpha level chosen to be .001

(b) Observation: 12 men jump, 3 are injured (this many or more injuries would occur only 46 times in a million when the true injury rate is .006).

(c) Conclusion: halt experiment - .000046 is less than .001.

#### PRODUCTION OF TABLE

Individual binomial probabilities for  $P = .006$ ;  $r = 0, 1, 7$ ;  $n = 1, 1, 50$  were computed on a Monroe Epic 2000 electronic calculator. An iterative procedure was used which, coupled with a biased roundoff in this machine, produced a maximum error of about  $.5 \times 10^{-12}$  for  $r = 0$ . The error for all other values of  $r$  was less than this amount. Individual probabilities to 8 significant digits were then summed for each  $n$  to verify that this summation was equal to unity. The printed terms of the summation were then used to produce the inclosed 6 place table of cumulated binomial probabilities for  $p = .006$ ;  $r = 0, 1, 6$ ;  $n = 1, 1, 50$ . The table was subsequently proof-read twice (independently) against the original printouts of the summations.

N	Zero	n (number injured)				N
		1 or more	2 or more	3 or more	4 or more	
1	.994000	.006000	-	-	-	1
2	.988036	.011964	.000036	-	-	2
3	.982108	.017892	.000108	.000000	-	3
4	.976215	.023785	.000214	.000001-	.000000	4
5	.970358	.029642	.000356	.000002	.000000	5
6	.964536	.035464	.000531	.000004	"	6
7	.958748	.041252	.000741	.000007	"	7
8	.952996	.047004	.000984	.000012	"	8
9	.947278	.052722	.001260	.000018	"	9
10	.941594	.058406	.001569	.000025	"	10
11	.935945	.064055	.001910	.000034	"	11
12	.930329	.069671	.002283	.000046	.000001-	12
13	.924747	.075253	.002687	.000059	.000001-	13
14	.919199	.080801	.003123	.000075	.000001	14
15	.913683	.086317	.003589	.000093	.000002	15
16	.908201	.091799	.004085	.000114	.000002	16
17	.902752	.097248	.004611	.000138	.000003	17
18	.897336	.102664	.005167	.000165	.000004	18
19	.891952	.108048	.005752	.000195	.000005	19
20	.886600	.113400	.006366	.000228	.000006	20
21	.881280	.118720	.007008	.000265	.000007	21
22	.875993	.124007	.007678	.000305	.000009	22
23	.870737	.129263	.008376	.000350	.000010	23
24	.865512	.134488	.009102	.000398	.000013	24
25	.860319	.139681	.009854	.000450	.000015	25



26	.855157	.144843	.010633	.000506	.000017	"	26
27	.850026	.149974	.011438	.000567	.000020	.000001-	27
28	.844926	.155074	.012269	.000632	.000024	.000001-	28
29	.839856	.160143	.013126	.000702	.000027	.000001-	29
30	.834817	.165183	.014008	.000777	.000031	.000001-	30
31	.829809	.170191	.014915	.000856	.000036	.000001	31
32	.824830	.175170	.015847	.000941	.000041	.000001	32
33	.819881	.180119	.016803	.001030	.000046	.000002	33
34	.814961	.185039	.017783	.001125	.000052	.000002	34
35	.810072	.189928	.018786	.001225	.000058	.000002	35
36	.805211	.194789	.019813	.001330	.000065	.000003	36
37	.800380	.199620	.020863	.001441	.000073	.000003	37
38	.795578	.204422	.021936	.001557	.000081	.000003	38
39	.790804	.209196	.023031	.001680	.000090	.000004	39
40	.786059	.213941	.024148	.001808	.000100	.000004	40
41	.781343	.218657	.025286	.001942	.000110	.000005	41
42	.776655	.223345	.026447	.002082	.000121	.000005	42
43	.771995	.228005	.027628	.002228	.000133	.000006	43
44	.767363	.232637	.028830	.002380	.000145	.000007	44
45	.762759	.237241	.030053	.002539	.000159	.000008	45
46	.758182	.241818	.031296	.002704	.000173	.000009	46
47	.753633	.246367	.032559	.002876	.000188	.000010	47
48	.749111	.250888	.033842	.003054	.000204	.000011	48
49	.744617	.255383	.035144	.003239	.000221	.000012	49
50	.740149	.259851	.036466	.003430	.000239	.000013	50

Probability of n Injuries Among N Jumpers (P = .006)

## References

1. Data for injury rates were provided by:
  - a. Safety Director, US Army Mobility Command, Warren, Mich.
  - b. Commanding General, 82nd Airborne Division, Ft Bragg, N. C.
  - c. Commanding Officer, 428th Medical Bn., Fort Benning, Georgia.
2. King, Robert D. FAA Aviation News. p 11, Vol 4, No. 11, March 1966.
3. Wald, A. Sequential Analysis, 1947, Wiley, N. Y.
4. Whittingham; cited in Bergin, K. G., Aviation Medicine, 1949, John Wright and Sons, Ltd, Bristol.

Unclassified

Security Classification

**DOCUMENT CONTROL DATA - R&D**

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) US Army Aeromedical Research Unit Fort Rucker, Alabama		2a REPORT SECURITY CLASSIFICATION Unclassified	
		2b GROUP	
3 REPORT TITLE EXPECTED INJURY RATES FOR EXPERIMENTAL AIRBORNE OPERATIONS			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5 AUTHOR(S) (Last name, first name, initial) Avner, R. A., 1st Lt., MSC			
6 REPORT DATE June 1966		7a TOTAL NO OF PAGES 6	7b NO OF REFS 4
8a CONTRACT OR GRANT NO		9a ORIGINATOR'S REPORT NUMBER(S) USAARU Report No. 66-7	
b PROJECT NO 3AO 2560 1A 819 c Task No. 036 (FY 66) d		9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10 AVAILABILITY LIMITATION NOTICES Distribution of this document is unlimited. Citation of names of commercial equipment or materials does not constitute an official endorsement or approval of the use of such items.			
11 SUPPLEMENTARY NOTES		12 SPONSORING MILITARY ACTIVITY US Army Medical Research and Development Command, Washington, D. C. 20315	
13 ABSTRACT  Probability of injury for Army paratroopers under conditions of full combat load and unprepared drop zone was estimated to be .006 (standard error = .002, N = 5,253). Tables were computed to allow tests of departure from this rate under experimental conditions involving up to 50 jumpers.			

DD FORM 1473  
1 JAN 64

Unclassified

Security Classification

FT RUCKER 066007

1A. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
<p>Aviation Medicine Parachuting Casualty Rate Experimental Design Applied Statistics</p>						

**INSTRUCTIONS**

**1. ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

**2a. REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

**2b. GROUP:** Automatic downgrading is specified in DoD Directive S200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

**3. REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

**4. DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

**5. AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

**6. REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

**7a. TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

**7b. NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

**8a. CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

**8b, 8c, & 8d. PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

**9a. ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

**9b. OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

**10. AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

**11. SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

**12. SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

**13. ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

**14. KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.